

Bay Area Air Quality Management District

939 Ellis Street
San Francisco, CA 94109
(415) 771-6000

MAJOR FACILITY REVIEW PERMIT

Issued To:
Western Fiberglass, Inc.
Facility #A7974

Facility Address:
1555 Copperhill Pkwy.
Santa Rosa, CA 95403

Mailing Address:
1555 Copperhill Pkwy.
Santa Rosa, CA 95403

Responsible Official:
Michael E. Lewis, President
(707) 523-2050

Facility Contact:
Frank Lillo
(707) 523-2050

Type of Facility: Fiberglass/Resin Operation
Primary SIC: 3088
Product: Fiberglass Products

ISSUED BY THE BAY AREA AIR QUALITY MANAGEMENT DISTRICT

Ellen Garvey, Air Pollution Control Officer

Date

TABLE OF CONTENTS

I. STANDARD CONDITIONS	1
II. EQUIPMENT LIST	5
A. PERMITTED SOURCE LIST	5
B. ABATEMENT DEVICE LIST	5
III. GENERALLY APPLICABLE EMISSION REQUIREMENTS	6
IV. <u>SOURCE-SPECIFIC</u> APPLICABLE REQUIREMENTS	10
V. SCHEDULE OF COMPLIANCE	18
VI. PERMIT CONDITIONS	18
A. SOURCE SPECIFIC PERMIT CONDITIONS	18
VII. APPLICABLE EMISSION LIMITS & COMPLIANCE MONITORING REQUIREMENTS	21
VIII. TEST METHODS	26
IX. GLOSSARY	27
X. APPENDIX A - APPLICABLE STATE IMPLEMENTATION PLAN	30

I. STANDARD CONDITIONS

A. Administrative Requirements

The permit holder shall comply with all applicable requirements in the following regulations:

BAAQMD Regulation 1 - General Provisions and Definitions

(as amended by the District Board on 11/3/93);

SIP Regulation 1 - General Provisions and Definitions

(as approved by EPA through 11/10/82);

BAAQMD Regulation 2, Rule 1 - Permits, General Requirements

(as amended by the District Board on 6/7/95);

SIP Regulation 2, Rule 1 - Permits, General Requirements

(as approved by EPA through 6/23/95);

BAAQMD Regulation 2, Rule 2 - Permits, New Source Review

(as amended by the District Board on 6/7/95);

SIP Regulation 2, Rule 2 - Permits, New Source Review and Prevention of Significant Deterioration

(as approved by EPA through 10/19/84); and

BAAQMD Regulation 2, Rule 4 - Permits, Emissions Banking

(as amended by the District Board on 6/15/94).

B. Conditions to Implement Regulation 2, Rule 6, Major Facility Review

1. This Major Facility Review Permit expires on [ENTER DATE 5 YEARS AFTER ISSUANCE]. The permit holder shall submit a complete application for renewal of this Major Facility Review Permit no later than [6 MONTHS PRIOR TO EXPIRATION] and no earlier than [ONE YEAR PRIOR TO EXPIRATION]. **If a complete application for renewal has not been submitted in accordance with these deadlines, the facility may not operate after** [DAY PRIOR TO EXPIRATION]. (Regulation 2-6-307, 404.2, & 409.6; MOP Volume II, Part 3, §4.2)
2. The permit holder shall comply with all conditions of this permit. The permit consists of this document and all appendices. Any non-compliance with the terms and conditions of this permit will constitute a violation of the law and will be grounds for enforcement action; permit termination, revocation and reissuance, or modification; or denial of a permit renewal application. (Regulation 2-6-~~307~~ 409.7; MOP Volume II, Part 3, §4.11)
3. In the event any enforcement action is brought as a result of a violation of any term or condition of this permit, the fact that it would have been necessary for the permittee to halt or reduce the permitted activity in order to maintain compliance with such term or condition shall not be a defense to such enforcement action. (MOP Volume II, Part 3, §4.11)
4. This permit may be modified, revoked, reopened and reissued, or terminated for cause. (Regulation 2-6-307, 409.8, 415; MOP Volume II, Part 3, §4.11)
5. The filing of a request by the facility for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated non-compliance does not stay the applicability of any permit condition. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)

I. Standard Conditions (continued)

6. This permit does not convey any property rights of any sort, nor any exclusive privilege. (Regulation 2-6-409.7; MOP Volume II, Part 3, §4.11)
7. The permit holder shall supply within 30 days any information that the District requests in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit ~~within 30 days~~. (Regulation 1-441, Regulation 2-6-409.4 & 501; MOP Volume II, Part 3, §4.11)
8. Any records required to be maintained pursuant to this permit which the permittee considers to contain proprietary or trade secret information shall be prominently designated as such. Copies of any such proprietary or trade secret information which are provided to the District shall be maintained by the District in a locked confidential file, provided, however, that requests from the public for the review of any such information shall be handled in accordance with the District's procedures set forth in Section 11 of the District Administrative Code. (Regulation 2-6-419; MOP Volume II, Part 3, §4.11)
9. Proprietary or trade secret information provided to EPA will be subject to the requirements of 40 CFR Part 2, Subpart B - Public Information, Confidentiality of Business Information. (40 CFR Part 2)
10. The emissions inventory submitted with the application for this Major Facility Review Permit is an estimate of actual emissions for the time period stated and is included only as one means of determining applicable requirements for emission sources. It does not establish, or constitute a basis for establishing, any new emission limitations. (MOP Volume II, Part 3, §4.11)

Minor Permit Modification Procedures

~~Notwithstanding the provisions set forth in Regulation 2, Rule 6, Major Facility Review, Section 411, Reports to EPA and Public Petitions for Major Facility Review Permits; Section 412, Public Participation, Major Facility Review Permit Issuance; and Section 414, Minor Permit Modification Procedures:~~

- ~~1. Advance public notice and EPA review shall not be required for any proposed minor permit modification. Once per calendar quarter, the District shall publish a list that includes any minor permit modification issued during the previous quarter.~~
- ~~2. For any minor permit modification involving an emission increase from any source or group of sources equal to or greater than: 5 tons per year of a regulated air pollutant; 2 tons per year of any single hazardous air pollutant; and 5 tons per year of any combination of hazardous air pollutants, the District shall provide to EPA a copy of each relevant application or a summary of the application, and a copy of each final permit revision.~~
- ~~3. For any minor permit modification involving an emission increase from any source or group of sources of less than: 5 tons per year of a regulated air pollutant, 2 tons per year of any single hazardous air pollutant; and 5 tons per year of any combination of hazardous air pollutants, the District shall not submit a copy of the relevant application, a summary of the application, or final permit revision to EPA. EPA shall not object to any permit modification involving an emission increase below the levels described herein. Such permit modifications shall be incorporated as attachments to this permit during the~~

I. Standard Conditions (continued)

~~remaining term of the permit, and incorporated into the body of the permit as part of the five-year permit renewal.~~

C. Requirement to Pay Fees

The permit holder shall pay annual fees in accordance with District Regulation 3, including Schedule P. (Regulation 2-6-402 & 409.13, Regulation 3; MOP Volume II, Part 3, §4.12)

D. Inspection and Entry

Access to Facility: The permit holder shall provide reasonable access to the facility and equipment which is subject to this permit to the APCO and/or to his or her designee. (Regulation 1-440, Regulation 2-6-409.3; MOP Volume II, Part 3, §4.14)

E. Records

Notwithstanding the specific wording in any requirement, all records for federally enforceable requirements shall be maintained for at least five years from the date of entry. (Regulation 2-6-501, Regulation 3; MOP Volume II, Part 3, §4.7)

F. Monitoring Reports

All required monitoring reports must be submitted to the District at least once every six months. All instances of non-compliance shall be clearly identified in these reports. The reports shall be certified by the responsible official as true, accurate, and complete. In addition, all instances of non-compliance with the permit shall be reported to the District's Compliance and Enforcement Division within 10 days of the discovery of the incident. Within 30 days of the discovery of any incident of non-compliance, the facility shall submit a written report including the probable cause of non-compliance and any corrective or preventative actions. (Regulation 2-6-502, Regulation 3; MOP Volume II, Part 3, §4.7)

G. Compliance Certification

Compliance certifications shall be submitted annually by the responsible official of this facility to the Bay Area Air Quality Management District and to the Environmental Protection Agency. The certification must list each applicable requirement, the compliance status, whether compliance was continuous or intermittent, the method used to determine compliance, and any other specific information required by the permit. The permit holder may satisfy this requirement through submittal of District-generated Compliance Certification forms. The certification should be directed to the District's Compliance and Enforcement Division, and a copy of the certification should be sent to the Environmental Protection Agency at the following address:

Director of the Air Division
USEPA, Region IX
75 Hawthorne Street
San Francisco, CA 94105
Attention: Air-3

(MOP Volume II, Part 3, §4.5 and 4.15)

H. Emergency Provisions

I. Standard Conditions (continued)

1. The permit holder may seek relief from enforcement action in the event of a breakdown, as defined by Regulation 1-208 of the District's Rules and Regulations, by following the procedures contained in Regulations 1-431 and 1-432. The District will thereafter determine whether breakdown relief will be granted in accordance with Regulation 1-433. (MOP Volume II, Part 3, §4.8)
2. The permit holder may seek relief from enforcement action for a violation of any of the terms and conditions of this permit caused by conditions beyond the permit holder's reasonable control by applying to the District's Hearing Board for a variance pursuant to Health and Safety Code Section 42350. The Hearing Board will determine after notice and hearing whether variance relief should be granted in accordance with the procedures and standards set forth in Health and Safety Code Section 42350 et seq. Any variance granted by the Hearing Board from any term or condition of this permit which lasts longer than 90 days will be subject to EPA approval. (MOP Volume II, Part 3, §4.8)
3. Notwithstanding the foregoing, the granting by the District of breakdown relief or the issuance by the Hearing Board of a variance will not provide relief from federal enforcement unless the Major Facility Review Permit has been modified pursuant to Regulation 2, Rule 6. (MOP Volume II, Part 3, §4.8)

I. Severability

In the event that any provision of this permit is invalidated by a court or tribunal of competent jurisdiction, or by the Administrator of the EPA, all remaining portions of the permit shall remain in full force and effect. (Regulation 2-6-409.5; MOP Volume II, Part 3, §4.10)

II. EQUIPMENT LIST

A. Permitted Source List

Each of the following sources has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits.

Table II-A

S-#	Description	Make or Type	Model	Capacity
S-1	Filament Winder	Durawound	Model 10-C	N/A
S-2	Closed Mold Vacuum	RTM Gun	Model 20210-00	N/A
S-3	Chopper Guns (2)	Glas-Craft	Model LPA-II-AAC	N/A

B. Abatement Device List

~~Each of the following abatement devices has been issued a permit to operate pursuant to the requirements of BAAQMD Regulation 2, Permits.~~

Table II-B

<u>A-#</u>	<u>Description</u>	<u>Source(s)</u> <u>Controlled</u>	<u>Applicable</u> <u>Requirement</u>	<u>Operating</u> <u>Parameters</u>	<u>Required</u> <u>Efficiency</u>
<u>A-1</u>	<u>Fiberglass Filters</u>	<u>S-2, S-3</u>	<u>BAAQMD</u> <u>Regulation</u> <u>6-301</u>		

A-#	Description	Make or Type	Model	Capacity
A-1	Filter	N/A	N/A	2" by 48ft ²

III. ~~GENERALLY APPLICABLE EMISSION~~ REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. These requirements apply in a general manner to the facility and/or to sources exempt from the requirement to obtain a District Permit to Operate. The District has determined that these requirements would not be violated under normal, routine operations, and that no additional periodic monitoring or reporting to demonstrate compliance is warranted. In cases where a requirement, in addition to being generally applicable, is also specifically applicable to one or more sources, the requirement and the source are also included in ~~Part Section IV, Source-Specific Applicable Requirements, and Part VI, Applicable Emission Limits & Compliance Monitoring Requirements,~~ of this permit.

The dates in parenthesis in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s):

† The date(s) of adoption or most recent amendment of the regulation by the District Board or, for SIP requirements

2. Any federal requirement, including a version of a District regulation that has been approved into the SIP:

† The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

Where an applicable requirement is a SIP requirement, the full language of the SIP requirement is included in Appendix A of this permit.

Table III

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved/ FE (Y/N)	Sources/Operations Covered
BAAQMD Regulation 1	General Provisions and Definitions (11/3/93)	N Y [†]	all
<u>SIP Regulation 1</u>	<u>General Provisions and Definitions (11/10/82)</u>	<u>Y</u>	
BAAQMD Regulation 4	Air Pollution Episode Plan (3/20/91)	<u>N</u>	facility
<u>SIP Regulation 4</u>	<u>Air Pollution Episode Plan (8/06/90)</u>	<u>Y</u>	
BAAQMD Regulation 5	Open Burning (11/2/94)	N Y [†]	facility

(continued)

III. Generally Applicable Emission Requirements (continued)

Table III (continued)

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved/ FE (Y/N)	Sources/Operations Covered
<u>SIP Regulation 5</u>	<u>Open Burning (5/3/84)</u>	<u>Y</u>	
BAAQMD Regulation 6	Particulate Matter and Visible Emissions (12/19/90)	<u>N</u>	
6-301	Ringelmann Number 1 Limitation	N⁺	all, except temporary sandblasting, open fires, and operations subject to BAAQMD §6-303, 304, or 306
6-303	Ringelmann Number 2 Limitation	Y	sources listed in subsections
6-305	Visible Particles	Y	all, except temporary sandblasting and open fires
6-310	Particulate Weight Limitation	Y	all, except temporary sandblasting and open fires
6-401	Appearance of Emissions	Y	all
<u>SIP Regulation 6</u>	<u>Particulate Matter and Visible Emissions (5/3/84)</u>	<u>Y</u>	
BAAQMD Regulation 7	Odorous Substances (3/17/82)	N	all
BAAQMD Regulation 8, Rule 1	Organic Compounds - General Provisions (6/15/94)	Y	solvent cleaning operations, except operations subject to Reg. 8-2 or 8-4 which meet minimum abatement requirements
BAAQMD Regulation 8, Rule 3	Organic Compounds - Architectural Coatings (12/20/95)	N Y⁺	application of architectural coating
<u>SIP Regulation 8, Rule 3</u>	<u>Organic Compounds - Architectural Coatings (11/16/83)</u>	<u>Y</u>	

III. Generally Applicable Emission Requirements (continued)

Table III (continued)

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved/ FE (Y/N)	Sources/Operations Covered
BAAQMD Regulation 8, Rule 16	Organic Compounds - Solvent Cleaning Operations (6/15/94)	<u>Y</u>	
8-16-111	Exemption, Wipe Cleaning	Y	wipe cleaning operations
8-16-114	Exemption, Emulsion or Solution Cleaners	Y	operations exclusively using emulsion or solution cleaners containing < 1 wt% VOC
8-16-115	Exemption, Small, Unheated Solvent Cleaning Equipment	Y	unheated equipment containing < 1 gal solvent or evaporative area < 1 ft²
8-16-118.2	Limited Exemption, Compound with Low Volatility – Cold Cleaners	Y	cold cleaners using low volatility compounds
8-16-119	Limited Exemption, Sealed Chamber Solvent Cleaners	Y	sealed chamber solvent cleaners
8-16-303	Cold Cleaner Requirements	Y	cold solvent cleaners
8-16-304	Trichloroethylene Limitation	Y	all solvent cleaning operations
8-16-501	Solvent Records	Y	all solvent cleaning operations, except cold cleaners using low volatility compounds
BAAQMD Regulation 8, Rule 49	Organic Compounds - Aerosol Paint Products (12/20/95)	N Y ⁺	application of or specifications for aerosol products
<u>SIP Regulation 8, Rule 49</u>	<u>Organic Compounds - Aerosol Paint Products (3/22/95)</u>	<u>Y</u>	
BAAQMD Regulation 8, Rule 51	Organic Compounds - Adhesive and Sealant Products (12/20/95)	N	application or specification of adhesive or sealant products
BAAQMD Regulation 11, Rule 2	Hazardous Pollutants - Asbestos Demolition, Renovation and Manufacturing (12/4/91)	Y	asbestos surfacing/coating, installation, demolition, disposal

III. Generally Applicable Emission Requirements (continued)

Table III (continued)

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved FE (Y/N)	Sources/Operations Covered
BAAQMD Regulation 12, Rule 4	Miscellaneous Standards of Performance - Sandblasting (7/11/90)	N Y [†]	non-permanent abrasive blasting operations
<u>SIP</u> <u>Regulation 12,</u> <u>Rule 4</u>	<u>Miscellaneous Standards of Performance - Sandblasting (9/2/81)</u>	<u>Y</u>	

IV. SOURCE-SPECIFIC APPLICABLE REQUIREMENTS

The permit holder shall comply with all applicable requirements, including those specified in the BAAQMD and SIP Rules and Regulations and other federal requirements cited below. The requirements cited in the following tables apply in a specific manner to the indicated source(s). The text of all permit conditions cited is included in Part V, Permit Conditions, of this permit. All other text may be found in the regulations themselves.

The dates in parenthesis in the Title column identify the versions of the regulations being cited and are, as applicable:

1. BAAQMD regulation(s):

† The date(s) of adoption or most recent amendment of the regulation by the District Board or, for SIP requirements

2. Any federal requirement, including a version of a District regulation that has been approved into the SIP:

† The most recent date of EPA approval of any portion of the rule, encompassing all actions on the rule through that date

The full text of each permit condition cited is included in Section VI, Permit Conditions, of this permit. Additionally, where an applicable requirement is a SIP requirement, the full language of the SIP requirement is included in Appendix A of this permit. All other text may be found in the regulations themselves.

**Table IV-A
S-1 Filament Winder**

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved/ <u>Federally Enforceable</u> (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 50	Organic Compounds - Polyester Resin Operations (12/20/95)		
8-50-110	Limited Exemption, Touch-up and Repair	Y	
8-50-220²	Volatile Organic Compound	N	
8-50-301	Process Requirements	Y	
8-50-301.1	Monomer ≤ 35 wt%	Y	
8-50-301.2	Vapor Suppressant & VOC Emission ≤ 60g/m ²	Y	
8-50-304	Corrosion-resistant Materials	Y	
8-50-305	Surface Preparation and Clean-up Solvent	Y	
8-50-305.1	Storage in Closed Containers	Y	

(continued)

IV. Source-Specific Applicable Requirements (continued)

Table IV-A (continued)

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved/ <u>Federally Enforceable</u> (Y/N)	Future Effective Date
8-50-305.2	Self-closing Containers, Disposal	Y	
8-50-305.3	Minimizing Organic Emissions from Spray Equipment Clean-up	Y	
8-50-305.4	Clean-up Solvent, VOC \leq 200g/liter	Y	
8-50-306	Equipment Requirements	Y	
8-50-307	Gel Coat Requirement	Y	
8-50-501	Records	Y	
8-50-501.1	List of Materials Used	Y	
8-50-501.2	List VOC Content of Materials Used	Y	
8-50-501.3	Vapor-suppressed Resin Records	Y	
8-50-501.4	Daily Usage Records	Y	
8-50-501.5	Record Retention for 24 months	Y	
SIP Regulation 8, Rule 50	PROVISIONS NO LONGER IN CURRENT DISTRICT RULE Organic Compounds—Polyester Resin Operations (5/8/95)		
8-50-220 ⁺	Volatile Organic Compound	Y ²	
BAAQMD Cond. #9303			
Part 1	Usage (basis: offsets , cumulative increase)	Y	
Part 2	Material Usage Specifications (basis: BACT , cumulative increase)	Y	
Part 3	Record Keeping (basis: cumulative increase, Regulation 2-6-501)	Y	
Part 3a	Daily Material Usage (basis: Regulation 8-50-501.4)	Y	

⁺ This section is a definition, not an applicable requirement. However, it affects the applicable requirements of the regulation. As it is the only difference between the SIP and BAAQMD regulation requirements, it has been included in the permit to explain the difference between the applicable requirements.

² This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.

IV. Source-Specific Applicable Requirements (continued)

Table IV-A (continued)

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved/ Federally Enforceable (Y/N)	Future Effective Date
Part 3b	List of Materials and Material Properties (basis: Regulation 8-50-501.1, 501.2, 501.3)	Y	
Part 3c	Monthly Material Usage Totals (basis: offsets, cumulative increase)	Y	
Part 4	Annual Review Available Vapor Suppressants/Low Monomer Resins (basis: BACT)	Y	

IV. Source-Specific Applicable Requirements (continued)

Table IV-B
S-2 Closed Mold Vacuum

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved/ Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Regulation 8, Rule 50	Organic Compounds - Polyester Resin Operations (12/20/95)		
8-50-110	Limited Exemption, Touch-up and Repair	Y	
8-50-203	Closed Mold System	N	
8-50-220 ²	Volatile Organic Compound	N	
8-50-301	Process Requirements	Y	
8-50-301.1	— Monomer ≤ 35 wt%	Y	
8-50-301.2	— Vapor Suppressant & VOC Emission $\leq 60\text{g/m}^2$	Y	
8-50-301.3	<u>Closed Mold System</u>	<u>Y</u>	
8-50-304	Corrosion-resistant Materials	Y	
8-50-305	Surface Preparation and Clean-up Solvent	Y	
8-50-305.1	Storage in Closed Containers	Y	
8-50-305.2	Self-closing Containers, Disposal	Y	
8-50-305.3	Minimizing Organic Emissions from Spray Equipment Clean-up	Y	
8-50-305.4	Clean-up Solvent, VOC $\leq 200\text{g/liter}$	Y	
8-50-307	Gel Coat Requirement	Y	
8-50-501	Records	Y	
8-50-501.1	List of Materials Used	Y	
8-50-501.2	List VOC Content of Materials Used	Y	
8-50-501.3	Vapor-suppressed Resin Records	Y	
8-50-501.4	Daily Usage Records	Y	
8-50-501.5	Record Retention for 24 months	Y	
SIP Regulation 8, Rule 50	PROVISIONS NO LONGER IN CURRENT RULE Organic Compounds - Polyester Resin Operations (5/8/95)		
8-50-220 ²	Volatile Organic Compound	Y ³	

(continued)

IV. Source-Specific Applicable Requirements (continued)

Table IV-B (continued)

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved/ Federally Enforceable (Y/N)	Future Effective Date
BAAQMD Cond #9303			
Part 5	Usage (basis: offsets , cumulative increase)	Y	
Part 6	Material Usage Specifications (basis: BACT , cumulative increase)	Y	
Part 7	Record Keeping (basis: cumulative increase, Regulation 2-6-501)	Y	
Part 7a	Daily Material Usage (basis: Regulation 8-50-501.4)	Y	
Part 7b	List of Materials and Material Properties (basis: Regulation 8-50-501.1, 501.2, 501.3)	Y	
Part 7c	Monthly Material Usage Totals (basis: offsets, cumulative increase)	Y	

² ~~This section is a definition, not an applicable requirement. However, it affects the applicable requirements of the regulation. As it is the only difference between the SIP and BAAQMD regulation requirements, it has been included in the permit to explain the difference between the applicable requirements.~~

³ ~~This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.~~

IV. Source-Specific Applicable Requirements (continued)

Table IV-C
S-3 Chopper Guns (2)

Applicable Requirement	Regulation Title or Description of Requirement	SIP approved/ Federally Enforceable (Y/N)	Future Effective Date
<u>BAAQMD</u>			
<u>Regulation 6</u>	<u>Particulate Matter and Visible Emissions (12/19/90)</u>		
<u>6-301</u>	<u>Ringelmann Number 1 Limitation</u>	<u>N</u>	
<u>6-305</u>	<u>Visible Particles</u>	<u>Y</u>	
<u>6-401</u>	<u>Appearance of Emissions</u>	<u>Y</u>	
<u>SIP</u>	<u>PROVISIONS NO LONGER IN CURRENT RULE</u>		
<u>Regulation 6</u>	<u>Particulate Matter and Visible Emissions (6/16/83)</u>		
<u>6-301</u>	<u>Ringelmann Number 1 Limitation</u>	<u>Y</u>	
<u>BAAQMD</u>			
<u>Regulation 8,</u>	<u>Organic Compounds - Polyester Resin Operations (12/20/95)</u>		
<u>Rule 50</u>			
8-50-110	Limited Exemption, Touch-up and Repair	Y	
8-50-220 ³	Volatile Organic Compound	N	
8-50-301	Process Requirements	Y	
8-50-301.1	Monomer ≤ 35 wt%	Y	
8-50-301.2	Vapor Suppressant & VOC Emission ≤ 60g/m ²	Y	
8-50-302	Spraying Operations	Y	
8-50-302.1	Airless Spray	Y	
8-50-302.2	Air-Assisted Airless Spray	Y	
8-50-302.3	Electrostatic Spray	Y	
8-50-302.4	HVLP	Y	
8-50-304	Corrosion-resistant Materials	Y	
8-50-305	Surface Preparation and Clean-up Solvent	Y	
8-50-305.1	Storage in Closed Containers	Y	
8-50-305.2	Self-closing Containers, Disposal	Y	
8-50-305.3	Minimizing Organic Emissions from Spray Equipment Clean-up	Y	

(continued)

IV. Source-Specific Applicable Requirements (continued)

Table IV-C (continued)

Applicable Requirement	Regulation Title or Description of Requirement	SIP-approved/ Federally Enforceable (Y/N)	Future Effective Date
8-50-305.4	Clean-up Solvent, VOC ≤ 200g/liter	Y	
8-50-307	Gel Coat Requirement	Y	
8-50-501	Records	Y	
8-50-501.1	List of Materials Used	Y	
8-50-501.2	List VOC Content of Materials Used	Y	
8-50-501.3	Vapor-suppressed Resin Records	Y	
8-50-501.4	Daily Usage Records	Y	
8-50-501.5	Record Retention for 24 months	Y	
SIP Regulation 8, Rule 50	PROVISIONS NO LONGER IN CURRENT RULE Organic Compounds – Polyester Resin Operations (5/8/95)		
8-50-220 ²	Volatile Organic Compound	Y ³	
BAAQMD Cond. #9303			
Part 8	Usage (basis: <u>offsets</u> , cumulative increase)	Y	
Part 9	Material Usage Specifications (basis: <u>BACT</u> , cumulative increase)	Y	
Part 10	Record Keeping (basis: cumulative increase, <u>Regulation 2-6-501</u>)	Y	
<u>Part 10a</u>	<u>Daily Material Usage (basis: Regulation 8-50-501.4)</u>	<u>Y</u>	
<u>Part 10b</u>	<u>List of Materials and Material Properties (basis: Regulation 8-50-501.1, 501.2, 501.3)</u>	<u>Y</u>	
<u>Part 10c</u>	<u>Monthly Material Usage Totals (basis: offsets, cumulative increase)</u>	<u>Y</u>	
Part 11	Annual Review Available Vapor Suppressants/Low Monomer Resins (basis: BACT)	Y	
Part 12	All Spray Operations Must Be In Building (basis: BACT <u>Regulation 6-301, 6-305</u>)	Y	
<u>Part 13</u>	<u>Only One Spray Gun May Be Operated At One Time (basis: BACT)</u>	<u>Y</u>	

IV. Source-Specific Applicable Requirements (continued)

² ~~This section is a definition, not an applicable requirement. However, if affects the applicable requirements of the regulation. As it is the only difference between the SIP and BAAQMD regulation requirements, it has been included in the permit to explain the difference between the applicable requirements.~~

³ ~~This section has been removed from BAAQMD Regulations because it has been superseded. Nevertheless, the source must comply with this regulation until US EPA has reviewed and approved (or disapproved) the District's revision of the regulation.~~

V. SCHEDULE OF COMPLIANCE

The permit holder shall continue to comply with all applicable requirements cited in Parts III and IV of this permit. The permit holder shall also comply with applicable requirements that become effective during the term of this permit.

VI. PERMIT CONDITIONS

Any condition that is preceded by an asterisk is not federally enforceable.

A. Source Specific Permit Conditions

Condition # 9303

For S-1, Filament Winder:

1. The net resin and cleanup solvent usage at S-1 shall not exceed the following limits during any consecutive 365 day period (a) 600 gallons cleaning solvent, (b) 20,000 gallons resin as applied; unless the operator can demonstrate to the satisfaction of the District, through daily recordkeeping and POC calculations, that precursor organic compound emissions from the operation of S-1 are below 7559 pounds during any consecutive 365 day period. (basis: Offsets, cumulative increase)
2. Only the following materials or their chemical equivalents shall be used at S-1.
Cleaning Solvent: Glas-Craft TGC FRP Tool and Gun Cleaner
Resin: Ashland Aropol L-5505T-20 Resin
Catalyst: Methyl Ethyl Ketone Peroxide
Before using an alternate material at S-1, the owner/operator shall first apply for and receive written approval from the District. (basis: BACT, cumulative increase)
3. To demonstrate compliance with the above conditions, the following records shall be kept on site and made available for District inspection for a period of at least ~~24 months~~ 5 years from the date on which a record was made. (basis: cumulative increase, Regulation 2-6-501)
 - a) The type and quantity of cleanup solvent, resin and catalyst used daily. The type and quantities of these materials used for touch-up and repair shall be logged separately. (basis: Regulation 8-50-501.4)
 - b) Maintain a list of resins and cleanup solvents including the weight % VOC, or monomer content, of the resin and the grams of VOC per liter of cleanup solvent. (basis: Regulation 8-50-501.1, 501.2, 501.3)
 - c) Monthly totals of daily quantities. (basis: Offsets, cumulative increase)
4. Western Fiberglass shall review, on an annual basis, the commercial availability of vapor suppressants and lower monomer content resins which could be used to

VI. Permit Conditions (continued)

manufacture corrosive resistant products at S-1, and shall use these products at S-1 as soon as they are available. Western Fiberglass shall submit the results of the commercial availability review to the District, each year prior to permit renewal. (basis: BACT ~~cumulative increase~~)

Condition # 9303 (continued)

For S-2, Closed Mold Vacuum:

5. The net resin and cleanup solvent usage at S-2 shall not exceed the following limits during any consecutive 365 day period (a) 600 gallons cleaning solvent, (b) 30,000 gallons resin as applied; unless the operator can demonstrate to the satisfaction of the District, through daily recordkeeping and POC calculations, that precursor organic compound emissions from the operation of S-2 are below 3453 pounds during any consecutive 365 day period. (basis: Offsets, cumulative increase)
6. Only the following materials or their chemical equivalents shall be used at S-2.
Cleaning Solvent: Glas-Craft TGC FRP Tool and Gun Cleaner
Resin: Ashland Aropol 7241 RT
Catalyst: Methyl Ethyl Ketone Peroxide
Before using an alternate material at S-2, the owner/operator shall first apply for and receive written approval from the District. (basis: BACT, cumulative increase)
7. To demonstrate compliance with the above conditions, the following records shall be kept on site and made available for District inspection for a period of at least ~~24 months~~ 5 years from the date on which a record was made. (basis: cumulative increase, Regulation 2-6-501)
 - a) The type and quantity of cleanup solvent, resin and catalyst used and recycled daily. The type and quantities of these materials used and recycled for touch-up and repair shall be logged separately. (basis: Regulation 8-50-501.4)
 - b) Maintain a list of resins and cleanup solvents including the weight % VOC, or monomer content, of the resin and the grams of VOC per liter of cleanup solvent. (basis: Regulation 8-50-501.1, 501.2, 501.3)
 - c) Monthly totals of daily quantities. (basis: Offsets, cumulative increase)

Condition # 9303 (continued)

For S-3, Chopper Guns

8. The net resin and cleanup solvent usage at S-3 shall not exceed the following limits during any consecutive 365 day period (a) 600 gallons cleaning solvent, (b) 30,000 gallons resin as applied; unless the operator can demonstrate to the satisfaction of the District, through daily recordkeeping and POC calculations, that precursor organic compound emissions from the operation of S-3 are below 15,814 pounds during any consecutive 365 day period. (basis: Offsets, cumulative increase)

VI. Permit Conditions (continued)

9. Only the following materials or their chemical equivalents shall be used at S-3.
Cleaning Solvent: Glas-Craft TGC FRP Tool and Gun Cleaner
Resin: Ashland Aropol L-5505T-20 Resin
Catalyst: Methyl Ethyl Ketone Peroxide
Before using an alternate material at S-3, the owner/operator shall first apply for and receive written approval from the District. (basis: BACT, cumulative increase)
10. To demonstrate compliance with the above conditions, the following records shall be kept on site and made available for District inspection for a period of at least ~~24 months~~ 5 years from the date on which a record was made. (basis: cumulative increase, Regulation 2-6-501)
 - a) The type and quantity of cleanup solvent, resin and catalyst used daily. The type and quantities of these materials used for touch-up and repair shall be logged separately. (basis: Regulation 8-50-501.4)
 - b) Maintain a list of resins and cleanup solvents including the weight % VOC, or monomer content, of the resin and the grams of VOC per liter of cleanup solvent. (basis: Regulation 8-50-501.1, 501.2, 501.3)
 - c) Monthly totals of daily quantities. (basis: Offsets, cumulative increase)
11. Western Fiberglass shall review, on an annual basis, the commercial availability of vapor suppressants and lower monomer content resins which could be used to manufacture corrosive resistant products at S-3, and shall use these products at S-3 as soon as they are available. Western Fiberglass shall submit the results of the commercial availability review to the District, each year prior to permit renewal. (basis: BACT)
12. The spray area and all associated spray operations shall be contained within the building. (basis: Regulation 6-301, 305 BACT)
13. ~~In no case, shall more than one chopper gun operate at any time. (basis: BACT)~~
[Comment: This condition was not imposed as a BACT measure, but due to the facility's request that the two spray guns be permitted as a single source, as opposed to two separate sources. For consistency with current policy allowing a single permit for a spray booth equipped with multiple spray guns, the District is proposing to delete this condition. This deletion will have no impact on the emission limits imposed by the original Permit to Operate.]

VII. APPLICABLE EMISSION LIMITS & COMPLIANCE MONITORING REQUIREMENTS

This section has been included only to summarize the applicable emission limits contained in Section IV, Source-Specific Applicable Requirements, of this permit. The following tables show the relationship between each emission limit and the associated compliance monitoring provisions, if any indicate the type of compliance monitoring required for each applicable emission limit. The monitoring frequency indicates whether periodic (P) or continuous (C) monitoring is required. For periodic monitoring, the frequency of the monitoring has also been shown, either annual (A), quarterly (Q), monthly (M), daily (D), or on an event basis (E). No monitoring (N) has been required if the current applicable rule or regulation does not require monitoring, and the operation is unlikely to deviate from the applicable emission limit based upon the nature of the operation.

Table VII-A
S-1 FILAMENT WINDER

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	Regulation 8-50-301.1	Y		monomer content ≤ 35% by weight	Regulation 8-50-501.2; <u>Cond #9303, part 3b</u>	P/ <u>E</u>	records
	Regulation 8-50-301.2	Y		weight loss/emissions ≤ 60 g/m ² surface area	Regulation 8-50-501.3; <u>Cond #9303, part 3b</u>	P/ <u>E</u>	records
	Regulation 8-50-304	Y		monomer content ≤ 50% by weight	Regulation 8-50-501.2; <u>Cond #9303, part 3b</u>	P/ <u>E</u>	records
	Regulation 8-50-305.4	Y		content of cleaning material ≤ 200 g/liter	Regulation 8-50-501.2; <u>Cond #9303, part 3b</u>	P/ <u>E</u>	records
	Regulation 8-50-307	Y		content of gel coat, as applied ≤ 250 g/liter	Regulation 8-50-501.2; <u>Cond #9303, part 3b</u>	P/ <u>E</u>	records

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Table VII-A
S-1 FILAMENT WINDER

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition #9303, Part 1	Y		7559 lbs per 365 consecutive days; <u>or</u> maximum cleaning solvent usage of 600 gallons and 20,000 gallons resin, as applied, per 365 day period	Regulation 8-50-501.4; <u>Cond #9303,</u> <u>parts 3a and 3c</u>	P/D	records

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Table VII-B
S-2 CLOSED MOLD VACUUM

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
VOC	Regulation 8-50-301.1	Y		monomer content \leq 35% by weight	Regulation 8-50-501.2	P	records
	Regulation 8-50-301.2	Y		weight loss/emissions \leq 60 g/m ² surface area	Regulation 8-50-501.3	P	records
VOC	Regulation 8-50-304	Y		monomer content \leq 50% by weight	Regulation 8-50-501.2; <u>Cond #9303, part 7b</u>	P/E	records
	Regulation 8-50-305.4	Y		content of cleaning material \leq 200 g/liter	Regulation 8-50-501.2; <u>Cond #9303, part 7b</u>	P/E	records
	Regulation 8-50-307	Y		content of gel coat, as applied \leq 250 g/liter	Regulation 8-50-501.2; <u>Cond #9303, part 7b</u>	P/E	records
	BAAQMD <u>Condition</u> #9303, Part 5	Y		3453 lbs per 365 consecutive days; <u>or</u> maximum cleaning solvent usage of 600 gallons and 30,000 gallons resin, as applied, per 365 day <u>period</u>	Regulation 8-50-501.4; <u>Cond #9303, parts 7a and 7c</u>	P/D	records

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Table VII-C
S-3 CHOPPER GUNS (2)

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
TSP	Regulation 6-301	Y		Ringelmann 1, or equivalent opacity, for more than 3 min/hr	None	N	
VOC	Regulation 8-50-301.1	Y		monomer content ≤ 35% by weight	Regulation 8-50-501.2; Cond #9303, part 10b	P/E	records
	Regulation 8-50-301.2	Y		weight loss/emissions ≤ 60 g/m ² surface area	Regulation 8-50-501.3; Cond #9303, part 10b	P/E	records
	Regulation 8-50-304	Y		monomer content ≤ 50% by weight	Regulation 8-50-501.2; Cond #9303, part 10b	P/E	records
	Regulation 8-50-305.4	Y		content of cleaning material ≤ 200 g/liter	Regulation 8-50-501.2; Cond #9303, part 10b	P/E	records
	Regulation 8-50-307	Y		content of gel coat, as applied ≤ 250 g/liter	Regulation 8-50-501.2; Cond #9303, part 10b	P/E	records

(continued)

VII. Applicable Emission Limits & Compliance Monitoring Requirements (continued)

Table VII-C
S-3 CHOPPER GUNS (2)

Pollutant	Emission Limit Citation	FE Y/N	Future Effective Date	Emission Limit	Monitoring Requirement Citation	Monitoring Frequency (P/C/N)	Monitoring Type
	BAAQMD Condition #9303 Part 8	Y		15814 lbs per 365 consecutive days; <u>or</u> <u>maximum cleaning</u> <u>solvent usage of 600</u> <u>gallons and 30,000</u> <u>gallons resin, as</u> <u>applied, per 365 day</u> <u>period</u>	Regulation 8-50-501.4; <u>Cond #9303,</u> <u>parts 10a and</u> <u>10c</u>	P/ <u>D</u>	records

VIII. TEST METHODS

The test methods associated with the emission limit of a District regulation are generally found in Section 600 of the regulation. The following table indicates only the test methods associated with the emission limits referenced in Section VII, Applicable Emission Limits & Compliance Monitoring Requirements, of this permit.

Table VIII

Applicable Requirement	Description of Requirement	Acceptable Test Methods	EPA Approved
<u>BAAQMD Regulation 6-301</u>	<u>Ringelmann No. 1 Limitation</u>	<u>Manual of Procedures, Volume I, Evaluation of Visible Emissions</u>	
<u>SIP Regulation 6-301</u>	<u>Ringelmann No. 1 Limitation</u>	<u>Manual of Procedures, Volume I, Evaluation of Visible Emissions</u>	
BAAQMD Regulation 8-50-301.1	Process Requirements, Monomer Content	Manual of Procedures, Volume III, Method 39, Determination of Styrene Monomer Content of Polyester Resin Material	✗
BAAQMD Regulation 8-50-301.2	Process Requirements, Vapor Suppressed Resins	Manual of Procedures, Volume III, Method 23, Determination of Volatile Emissions from Polyester Resins	✗
BAAQMD Regulation 8-50-304	Corrosion-resistant Materials	Manual of Procedures, Volume III, Method 23, Determination of Volatile Emissions from Polyester Resins	✗
BAAQMD Regulation 8-50-305.4	Surface Preparation and Clean-up Solvent, VOC Content	Manual of Procedures, Volume III, Method 31, Determination of Volatile Organic Compounds in Paint Strippers, Solvent Cleaners, and Low Solids Coatings	✗
BAAQMD Regulation 8-50-307	Gel Coat Requirement	Manual of Procedures, Volume III, Method 26, Determination of Volatile Weight Loss of Gel Coats	✗

IX. GLOSSARY

BAAQMD

Bay Area Air Quality Management District

BACT

Best Available Control Technology

Basis

The underlying authority which allows the District to impose requirements.

CAA

The federal Clean Air Act

CEQA

California Environmental Quality Act

CFR

The Code of Federal Regulations. 40 CFR contains the implementing regulations for federal environmental statutes such as the Clean Air Act. Parts 50-99 of 40 CFR contain the requirements for air pollution programs.

Cumulative Increase

The sum of permitted emissions from each new or modified source since a specified date pursuant to BAAQMD Rule 2-1-403, Permit Conditions (as amended by the District Board on 7/17/91) and SIP Rule 2-1-403, Permit Conditions (as approved by EPA on 6/23/95). Used to determine whether threshold-based requirements are triggered.

District

The Bay Area Air Quality Management District

EPA

The federal Environmental Protection Agency.

Excluded

Not subject to any District Regulations.

Federally Enforceable, FE

All limitations and conditions which are enforceable by the Administrator of the EPA including those requirements developed pursuant to 40 CFR Part 51, subpart I (NSR), Part 52.21 (PSD), Part 60, (NSPS), Part 61, (NESHAPs), Part 63 (HAP), and Part 72 (Permits Regulation, Acid Rain), and also including limitations and conditions contained in operating permits issued under an EPA-approved program that has been incorporated into the SIP.

VIII

IX. Glossary (continued)

HAP

Hazardous Air Pollutant. Any pollutant listed pursuant to Section 112(b) of the Act. Also refers to the program mandated by Title I, Section 112, of the Act and implemented by both 40 CFR Part 63, and District Regulation 2, Rule 5.

Major Facility

A facility with potential emissions of regulated air pollutants greater than or equal to 100 tons per year, greater than or equal to 10 tons per year of any single hazardous air pollutant, and/or greater than or equal to 25 tons per year of any combination of hazardous air pollutants, or such lesser quantity as determined by the EPA administrator.

MFR

Major Facility Review. The District's term for the federal operating permit program mandated by Title V of the Act and implemented by District Regulation 2, Rule 6.

MOP

The District's Manual of Procedures.

NESHAPs

National Emission Standards for Hazardous Air Pollutants. Contained in 40 CFR Part 61.

NMHC

Non-methane Hydrocarbons

NSR

New Source Review. A federal program for preconstruction review and permitting of new and modified sources of air pollutants for which the District is classified "non-attainment". Mandated by Title I of the Clean Air Act and implemented by 40 CFR Parts 51 and 52 as well as District Regulation 2, Rule 2. (Note: There are additional NSR requirements mandated by the California Clean Air Act.)

Offset Requirement

A New Source Review requirement to provide federally enforceable emission offsets at a specified ratio for the emissions from a new or modified source and any pre-existing cumulative increase minus any on site contemporaneous emission reduction credits. Applies to emissions of POC, NOx, PM10, and SO2.

POC

Precursor Organic Compounds

VIII

IX. Glossary (continued)

PM

Total Particulate Matter

PM10

Particulate matter with aerodynamic equivalent diameter of less than or equal to 10 microns

PSD

Prevention of Significant Deterioration. A federal program for permitting new and modified sources of air pollutants for which the District is classified "attainment" of the National Air Ambient Quality Standards. Mandated by Title I of the Act and implemented by both 40 CFR Part 52 and District Regulation 2, Rule 2.

SIP

State Implementation Plan. State and District programs and regulations approved by EPA and developed in order to attain the National Ambient Air Quality Standards. Mandated by Title I of the Act.

Title V

Title V of the federal Clean Air Act. Requires a federally enforceable operating permit program for major and certain other facilities.

VOC

Volatile Organic Compounds

Units of Measure:

g	=	grams
gal	=	gallon
hr	=	hour
lb	=	pound
in	=	inches
max	=	maximum
m ²	=	square meter
min	=	minute
psia	=	pounds per square inch, absolute
scfm	=	standard cubic feet per minute
yr	=	year

Facility Name: Western Fiberglass, Inc.
Proposed Permit for Facility #: A7974
Expiration Date: xx-xx-01
ID: KT

X. APPENDIX A - APPLICABLE STATE IMPLEMENTATION PLAN

See Attachment